

07/31/00
jc853 U.S. PRO

08-02-00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Patrick H. Dussud
Docket: MS146913.1/40062.79-US-01
Title: METHOD AND SYSTEM FOR MULTIPROCESSOR GARBAGE COLLECTION

jc869 U.S. PTO
09/628477
07/31/00

CERTIFICATE UNDER 37 CFR 1.10

'Express Mail' mailing label number: EL387614714US

Date of Deposit: July 31, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231

By: *Alicia R. Espinoza*
Name: Alicia R. Espinoza

BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

We are transmitting herewith the attached:

- ☒ Transmittal sheet, in duplicate, containing Certificate under 37 CFR 1.10.
- ☒ Utility Patent Application: Spec. 25 pgs; 20 claims; Abstract 1 pgs.
The fee has been calculated as shown below in the 'Claims as Filed' table.
- ☒ 5 sheets of formal drawings
- ☒ A signed Combined Declaration and Power of Attorney
- ☒ Assignment of the invention to Microsoft Corporation, Recordation Form Cover Sheet
- ☒ A check in the amount of \$924.00 to cover the Filing Fee
- ☒ A check for \$40.00 to cover the Assignment Recording Fee.
- ☒ Return postcard

CLAIMS AS FILED

Number of Claims Filed		In Excess of:		Number Extra		Rate		Fee
Basic Filing Fee								\$690.00
Total Claims								
20	-	20	=	0	x	18.00	=	\$0.00
Independent Claims								
6	-	3	=	3	x	78.00	=	\$234.00
MULTIPLE DEPENDENT CLAIM FEE								\$0.00
TOTAL FILING FEE								\$924.00

Please charge any additional fees or credit overpayment to Deposit Account No. 13-2725. A duplicate of this sheet is enclosed.

MERCHANT & GOULD P.C.
P.O. Box 2903, Minneapolis, MN 55402-0903
(303) 357-1648

By: *Timothy B. Scull*
Name: Timothy B. Scull
Reg. No.: 42,137
Initials: TBS



(PTO TRANSMITTAL - NEW FILING)

5 **METHOD AND SYSTEM FOR**
 MULTIPROCESSOR GARBAGE COLLECTION

Technical Field

 The present invention relates to methods and systems for the automatic
reclamation of allocated memory, normally referred to as "garbage collection." More
10 particularly, the present invention relates to garbage collection for multiprocessor
environments.

Background of the Invention

 Many computer systems, such as server systems, use a plurality of processing
units or microprocessors to increase the overall processing power of the computer system.
15 In a multiprocessor system, the separate processing units may often share the operating
memory of the system.

 In typical shared memory systems, a memory manager allocates memory to a
requesting program and performs the process of garbage collection for that program.
However, when garbage collection operations were performed on a memory in the
20 multiple processor environment, the garbage collection was performed by one processor.
All other processors were paused until the garbage collection operation was complete.
This was done to prevent access by one processor to the shared memory while another
processor was cleaning up the memory. As a result the efficiency of the multiple
processor systems is significantly reduced due to the idle time of the unused processors
25 during garbage collection.

It is with respect to these considerations and others that the present invention has been made.

Summary of the Invention

The present invention relates to garbage collection in a multiprocessor environment having a shared memory wherein two or more processing units participate in the reclamation of garbage memory objects. The shared memory is divided into regions or heaps and all heaps are dedicated to one of the participating processing units. The processing units generally perform garbage collection operations, i.e., a thread on the heap or heaps that are dedicated to that the processing unit. However, the processing units are also allowed to access and modify other memory objects, in other heaps when those objects are referenced by and therefore may be traced back to memory objects within the processing units dedicated heap.

Since processing units may access and modify objects in other heaps, the processing units must be synchronized. Synchronization occurs following predetermined phases of the garbage collection process, at "rendezvous points." In an embodiment of the invention, each garbage collection thread operates in four phases – marking, planning, relocation and compaction. The rendezvous points are at the ends of each phase. Each garbage collection thread will wait for all the other garbage collection threads to complete the present phase before beginning the next phase.

In an embodiment of the invention, since objects may reference across heaps, a reference is written to a directory when an object, referenced by an object in another heap, is relocated in a heap. Thus, during the relocation phase, not only is the new

location of an object in its heap written, but also a pointer to the new location of the object is written for those objects referenced by objects in other heaps.

The present invention relates to a system and method of collecting garbage in a computer system having a memory and a plurality of multiprocessors that share the memory. In general, the memory is logically viewed by the application program as one heap but it is divided into a plurality of heaps, each heap dedicated to one processor for garbage collection. Using the plurality of heaps, a plurality of garbage collection phases are performed, wherein each processor having a dedicated heap performs each of the phases using a garbage collection thread executing on the processor. Moreover, the processors are synchronized so that each processor has completed the preceding phase prior to beginning the next phase. The synchronizing act may wait for the other processors to complete the phase of the garbage collection process and once the other processors have completed the phase of the garbage collection process, beginning the next phase of the garbage collection process.

In accordance with other aspects, the present invention relates to a method of garbage collection that occurs in phases, such as a marking phase that marks all reachable objects in memory, a planning phase that plans the relocation of the object, a relocation phase that updates the object references based on information calculated by the planning phase, and a compaction phase that compacts the reachable objects in memory. The marking phase marks objects independently of the heap boundaries. The planning phase may further maintain a directory of object references for use during the relocation phase. The relocation phase analyzes each memory object to retrieve references to other memory objects. If a reference to another memory object is present, that reference information is

analyzed to determine which heap the referenced object is associated. Next, the directory for that heap is analyzed to determine a new address location of the referenced object so that the reference information in the memory object may be updated.

In accordance with yet other aspects, the method stops executing process threads prior to performing the marking phase. In order to execute the threads for the different phases, parallel threads are initiated in each processing unit that is associated with a memory heap. Upon completion of all garbage collection threads for a phase, parallel threads are then restarted for the next phase.

The invention may be implemented as a computer process, a computing system or as an article of manufacture such as a computer program product. The computer program product may be a computer storage medium readable by a computer system and encoding a computer program of instructions for executing a computer process. The computer program product may also be a propagated signal on a carrier readable by a computing system and encoding a computer program of instructions for executing a computer process.

A more complete appreciation of the present invention and its improvements can be obtained by reference to the accompanying drawings, which are briefly summarized below, and to the following detailed description of presently preferred embodiments of the invention, and to the appended claims.

Brief description of the Drawings

Fig. 1 illustrates a computer system incorporating a garbage collector of the present invention.

Fig. 2 illustrates functional software components of the present invention, including the garbage collector incorporated in the system shown in Fig. 1.

Fig. 3 is a flow diagram showing the operational characteristics performed by the garbage collector shown in Fig. 1 in accordance with the present invention.

5 Fig. 4 is a flow diagram showing the operational characteristics performed by an alternative embodiment of the garbage collector shown in Fig. 1 in accordance with the present invention.

Fig. 5 a time analysis indicating the timing of the operational characteristics of an example of a garbage collection process performed by the garbage collector shown in Fig.
10 2.

Detailed Description of the Invention

A computer system 20 that performs a process of reclaiming unused memory portions, pages or objects (collectively referred to herein as "objects") that are allocated to application programs or other processes, i.e., garbage collection, according to the
15 present invention is shown in Fig. 1. The system 20 has multiple processors 22 and a shared memory 24. In an embodiment of the invention, the system has two processors 22a and 22b as shown in Fig. 1, but in other embodiments, the system may have more than two processors. The processors 22 share the same memory 24 and each of the
processors 22 performs garbage collection over predetermined portions of the memory 24
20 in accordance with the present invention, as described below. In alternative embodiments having more than two processing units, all processing units may perform garbage collection but not all processing units are required to participate in garbage collection. Indeed, while more than one processing unit participates in garbage collection, any

number of units could be used for this process.

In its most basic configuration, computing system 20 is illustrated in Fig. 1 by dashed line 26. Additionally, system 20 may also include additional storage (removable and/or non-removable) including, but not limited to, magnetic or optical disks or tape.

5 Such additional storage is illustrated in Fig. 1 by removable storage 28 and non-removable storage 30. Computer storage media includes volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Memory 24, removable storage 28 and non-removable storage 30
10 are all examples of computer storage media. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by system
15 20. Any such computer storage media may be part of system 20. Depending on the configuration and type of computing device, memory 24 may be volatile, non-volatile or some combination of the two.

System 20 may also contain communications connection(s) 32 that allow the device to communicate with other devices. Communications connection(s) 32 is an
20 example of communication media. Communication media typically embodies computer readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media. The term “modulated data signal” means a signal that has one or more of

its characteristics set or changed in such a manner as to encode information in the signal.

By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. The term computer readable media as used herein
5 includes both storage media and communication media.

System 20 may also have input device(s) 34 such as keyboard, mouse, pen, voice input device, touch input device, etc. Output device(s) 36 such as a display, speakers, printer, etc. may also be included. All these devices are well known in the art and need not be discussed at length here.

10 Computer system 20 typically includes at least some form of computer readable media. Computer readable media can be any available media that can be accessed by system 20. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media includes volatile and nonvolatile, removable and non-removable media implemented in
15 any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any
20 other medium which can be used to store the desired information and which can be accessed by system 20. Communication media typically embodies computer readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information

delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of any of the above should also be included within the scope of computer readable media.

Fig. 2 illustrates a suitable software environment 40 of functional software components in which the present invention may be implemented. The software environment 40 is only one example of a suitable environment and is not intended to suggest any limitation as to the scope of use or functionality of the invention. Other well-known environments, and/or configurations that may be suitable for use with the invention may implement the present invention.

The software environment 40 incorporates a runtime environment 42 that incorporates aspects of the present invention. The environment 40 has a runtime environment 42 that operates to execute application programs and processes, such as application program 44. The application program 44 may communicate directly with the runtime environment or communicate through an application program interface, such as application program interface 46 shown in Fig. 1.

The runtime environment 42 incorporates at least two memory managers 48, such as memory managers 48a and 48b, each having a garbage collector module 50, such as garbage collector modules 50a and 50b. In alternative embodiments, the garbage collectors 50 may not be in memory managers, and may even be separate applications apart from the runtime environment. Although the garbage collectors may be separate

from the memory managers, a plurality of separate garbage collector processes are collectively used to perform garbage collection in environment 40. In an embodiment of the invention, each memory manager 48a and 48b is associated with one processing unit, such as 22a and 22b (Fig. 1), respectively. In other embodiments, other combinations of memory managers and processing units may be used. Moreover, in an embodiment, the process of garbage collection is provided as a service by the runtime environment. In other embodiments, the garbage collection may be a separate processing thread separate from the runtime environment.

The runtime environment 42 also incorporates a shared memory 52. The shared memory, which is the portion of memory that maintains allocated memory for the application program 44 and other running applications or processes (not shown). The memory portion 52 is divided into heaps 54. A heap may be a contiguous array of memory objects 56 or it may be organized into a set of discontinuous memory objects 56. The heap portions may be based on physical address space wherein the entire memory equally divided and each processor is assigned a portion or the heaps may be configured dynamically based on processor needs and/or other factors. Either way, by the time the process begins garbage collection, the portions of memory that each processor is responsible is known or readily determinable by the processor and is therefore, predetermined.

The memory objects 56 contain data and other information for use by the application 44. Additionally, the memory objects may contain object reference information relating to other memory objects 56. Moreover, the memory object reference information may relate to objects 56 within the same heap or within another heap 54.

Arrows 58 indicate such cross-heap references. Object references therefore have information related to both the heap for the referenced object and the address location within the heap.

In an embodiment of the invention, the memory is divided into as many heaps as there are processing units 22 (Fig. 1). Therefore, each processing unit 22 can manage and maintain a predetermined portion or heap of the memory. In this embodiment, memory managers 48a and 48b are associated with different processing units and therefore each memory manager maintains a different heap 54 from the other memory manager. Thus, each processing unit, such as 22a and 22b, is associated with a particular heap, such as 54a and 54b, respectively, such that the heap 54a is dedicated to the processing unit 22a and heap 54b is dedicated to processing unit 22b through memory managers 48a and 48b. The memory managers 48a and 48b communicate with each other as indicated by arrow 60 in order to synchronize various operations such as memory allocation and garbage collection.

As stated above, the present invention is embodied in garbage collection operations in a multiprocessor environment, such as environment 20 shown in Fig. 1, wherein the memory is divided into heaps 54 as shown in Fig. 2. An embodiment of the invention involves using all processing units 22 to collect garbage objects. In order to do so, the units 22 use garbage collector modules 50 to collect garbage objects within an assigned heap 54 of memory. Moreover, to accommodate cross-heap referenced memory objects, each garbage collector marks 50 objects independently of which heap 54 the object may reside. The activities of the different garbage collectors are synchronized following the mark phase. The synchronization or rendezvous allows all garbage

collectors 50 to complete marking all reachable objects before any one collector 50 proceeds to the next phase so that unmarked objects are not inadvertently reclaimed. Similar rendezvous or synchronization events occur at the end of each phase of the garbage collection process, as described below.

5 The present invention may be described in the general context of computer-executable instructions, such as program modules, executed by one or more computers or other devices. Generally, program modules include routines, programs, object-oriented-type objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Typically the functionality of the program modules may be
10 combined or distributed as desired in various embodiments. Additionally, the logical operations of the various embodiments of the present invention may also be partially or wholly implemented as interconnected hardware or logic modules within the computing system. The implementation is a matter of choice dependent on the performance requirements of the computing system implementing the invention. Accordingly, the
15 logical operations making up the embodiments of the present invention described herein are referred to alternatively as operations, steps or modules.

With respect to the garbage collector modules 50, shown in Fig. 2, the modules perform a number of operations or phases in order to reclaim the memory. In an embodiment of the invention, typical phases may be marking and sweeping or copying
20 the memory objects. Alternative embodiments may have other phases. The flow 60 of logical operations performed by the garbage collectors 50 during a collection session is shown in Fig. 3. In an embodiment, one of the memory managers 48 initiates the flow 60 once a predetermined amount of memory has been allocated. In other embodiments, one

of the other modules initiates the garbage collection flow 60, such as the garbage collector 50 or the runtime environment 42. Other modules or processes could be used to monitor memory use and initiate garbage collection when necessary.

The flow 60 begins with pause operation 62, which pauses any interfering processes and/or threads. Interfering processes or threads are any executing processes, such as applications, that use the shared memory. Additionally, other processes that may interfere with processing time may also be paused. Stopping or pausing interfering processes or threads is known to those skilled in the art since the processes must be stopped to perform garbage collection whether using one or multiple processors to carry out the garbage collection.

Once the interfering processes or threads are paused, the perform first/next phase operation 64 performs the first phase of the garbage collection process. In an embodiment, the first phase involves examining the roots of a dedicated heap of memory objects. Each processing unit operates on one heap of information. However, if necessary, the processing units can reach and modify objects located on other, non-dedicated heaps. Therefore, operation 64 relates to multiple garbage collection processing threads operating in parallel on different heaps of information.

As each garbage collection processing thread completes the first phase of the garbage collection process, test operation 66 tests whether the remaining garbage collection process threads have completed the first phase of the garbage collection process. If not flow branches NO to a wait state operation 74, which forces the process to wait a cycle or two and then branches back to test operation 66.

Once all garbage collection process threads have completed the first phase of the

garbage collection process, test operation 66 causes flow to branch YES to test operation 68. Test operation 68 determines whether all the garbage collection phases are completed. If so, then the garbage objects have been collected and flow branches YES to restart operation 70. Restart operation 70 restarts any processes that were paused at operation 62. Once the processes are restarted, flow 60 ends at 72.

If test operation 68 determines that there are more garbage collection phases to be done, then flow branches NO back to perform first/next phase operation 64. Operation 64 performs the next garbage collection phase necessary to complete the garbage collection process. In an embodiment, the next phase relates to sweeping the memory for garbage objects. In other embodiments, such as one discussed below, there are several phases that need to be completed before the garbage collection process is completed. Once operation 64 performs the next phase of the process flow continues as before through test operations 66 and 68 until all operations are complete.

Before the next phase is started, however, test operation 66 ensures that all garbage-collection processing threads have completed the preceding phase. The purpose behind waiting for all threads to be complete is to prevent one thread from performing the next phase of the garbage collection process on its own heap before another thread makes necessary modifications to any garbage-collection related memory in the heap. Since some garbage-collection memory in its heap may eventually be used by another thread, each thread must wait for the other threads to complete the preceding phase before starting the next phase.

Another embodiment of the present invention is shown in Fig. 4. Flow 100 begins with pause operation 102, which pauses any executing application program, such

as application program 44 (Fig. 2) or any other running process that uses memory and must be stopped during the marking phase. In essence, any program threads interfering with the heaps 54 are stopped or paused. Pause operation 102 is similar to pause operation 62 described above.

5 Once the interfering processes or threads are paused, one garbage collection thread process for each processing unit 22 is initiated. That is, following the pause operation 102, threads 104a and 104b are started wherein each thread is associated with one processing unit 22 (Fig. 1) and one heap 54 (Fig. 2). For the purposes of the following description, memory manager 48a and garbage collector 50a is associated with
10 processing unit 22a to perform thread 104a on dedicated heap 54a. Similarly, heap 54b is dedicated to memory manager 48b and collector 50b, which are associated with processing unit 22b that performs thread 104b. In embodiments having more than two processing units, a thread 104 for each of the additional processing units is implemented.

 With respect to thread 104a, the logical operations begin with mark operation 106.
15 Mark operation 106 locates and marks the roots of the processing threads associated with the heap 54 dedicated to garbage collection thread 104a. During the mark operation, each memory object that is referenced by a root is analyzed to determine if the memory object references another memory object. If so, the next referenced memory object is then analyzed. Additionally, if the memory object that is referenced, either by a root or by
20 another memory object is in a non-dedicated heap 54b, i.e., a heap that is not the dedicated heap, such as 54a, then the mark operation still traverses and marks the memory object. Thus, the mark operation 106 traces memory objects relatively independently of the heap boundaries. The only exception is that the operation does not

begin traces using root information from other heaps.

With respect to the algorithms used to trace the reachable objects, many different algorithms may be implemented in accordance with principles of the present invention.

In an embodiment, mark operation 106 recursively traverses the memory objects,

5 beginning at the first root reference and traverse each pointer representation, and marks each item that is visited until all object references beginning from the root reference are exhausted. Once exhausted, the process proceeds to the next root reference, again traversing each pointer reference and marking each visited object as visited. The same process continues until all root references, and their associated, reachable memory objects
10 are marked as reachable, i.e., live.

In alternative embodiments, recursion is replaced by other methods of tracing objects referenced by either the roots or other objects, such as through the use of iterative loops and auxiliary data structures. In such as case, an auxiliary stack can be used to store pointer information to live objects that have not been visited. As items are popped
15 from the stack, each item is analyzed to determine whether it has referenced other objects, and then it is removed from the stack and marked as visited. If a popped item references another object, information related to the referenced to object is placed on the stack as live and unvisited and that object is deemed live and unvisited. The operations continue until the stack is empty.

20 With respect to marking, there are many acceptable methods of marking memory objects. That is, for the purposes of the present invention, practically any marking scheme that effectively identifies the live objects as live may be used. For example, a single bit can be changed to indicate marked or unmarked. In an alternative embodiment,

references to the live objects could be stored in a data structure and later used during the clean up or sweep portion of the garbage collection.

While marking operation 106 is being performed by thread 104a, thread 104b performs mark operation 108. Since thread 104b is performed by processing unit 22b (Fig. 1), this thread may operation substantially concurrently with thread 104a described above. Functionally, mark operation 108 is the same as mark operation 106 described above. The only difference is that mark operation 108 begins marking objects using root information from a different dedicated heap, such as heap 54b instead of heap 54a, which is dedicated to thread 104a. Therefore, mark operation 108 marks all reachable objects originating from roots within heap 54b independently of the actual heap location for the objects.

Since marking operation 106 and 108 only set or mark objects as visited, i.e., the operations 106 and 108 do not clear objects or otherwise mark objects as not visited, conflicts related to both operations 106 and 108 attempting to mark the same object are of little concern. More specifically, if one operation, such as 106, reaches and marks the object before the other operation, such as 108, then operation 108 simply notices that the object is marked and does nothing further regarding the marked object. Similarly, if operation 108 marked the object and then operation 106 reached the object, operation 106 would notice that the object is marked and do nothing further regarding the marked object. If, however, both operations 106 and 108 reach the object at the same time, then both operations would mark the object and analyze its object references and proceed to the next object. The object marked as visited by two operations is not treated differently than if marked by only one operation. As both operations trace the same sub-objects, i.e.,

objects referenced by the marked object, one processor will most likely be faster than the other so that eventually one operation will reach and mark the next object before the other arrives. Once this occurs the later operation stops tracing sub-objects and any inefficiencies of dual tracing are reduced.

5 Referring back to thread 104a, once the reachable objects in shared memory are marked by operation 106, rendezvous point or operation 110 temporarily pauses the garbage collection operations. Similarly, rendezvous point 112 temporarily pauses thread 104b following the mark operation 108. Rendezvous points 110 and 112 are collections of operations that effectively pause or disable the garbage collection process threads 104a
10 and 104b, respectively, until any other garbage collection process thread or threads have finished marking memory objects in the shared memory that are reachable from the root information located in the dedicated heaps for those threads. The rendezvous points 110 and 112 may deliver and receive information to and from the other rendezvous points, such as 112 and 110, respectively, to communicate necessary information related to
15 whether each thread has completed the marking process.

Once it is determined, at point 110, that all other threads have completed their respective mark operations, such as mark operation 108 for thread 104b, plan operation 114 plans the relocation and compaction scheme for the dedicated heap 54a. Plan operation, analyzes the locations of the marked objects in the heap 54a, whether marked
20 by mark operation 108 or 110, and plans the new physical locations for the memory objects. For instance, plan operation 114 may determine the sizes of any gaps between marked objects, and elects to position a plug having the same size within that gap.

Otherwise, the plan operation 114 may simply determine the new memory addresses for

the memory objects as the objects are logically slid toward one direction, eliminating any existing gaps.

Plan operation 114 may create an additional data structure or directory related to object references that reference memory objects located in other heaps. Other threads
5 may then use this information during other phases of garbage collection for their respective heaps.

With respect to thread 104b, once rendezvous operation 112 determines that all the other threads, such as 104a, have completed their respective marking operations, then plan operation 116 begins. Plan operation 116 operates on heap 54b to perform the same
10 planning function as plan operation 114 performed on heap 54a. Plan operation 116 may follow the same algorithms for calculating new memory addresses as operation 114 discussed above. Alternatively, the planning phase may use different planning procedures to relocate the memory objects 116. Even if plan operation 116 uses different algorithms than plan operation 114, plan operation 116 still determines the new memory
15 addresses for the memory objects that are to be moved.

Following the planning operations 114 and 116, rendezvous points 118 and 120 temporarily pause threads 104a and 104b, respectively, until all other planning phases are completed. Rendezvous points 118 and 120 are similar to points 110 and 112 in that rendezvous points 118 and 120 may deliver and receive information to and from the other
20 rendezvous points, such as 120 and 118, respectively, to communicate necessary information related to whether each thread has completed the preceding process.

Referring to thread 104a, once rendezvous point 118 determines that all other threads have completed their respective plan operations, relocate operation 122 relocates

the object references within each memory object in the dedicated heap that references other objects. In other words, memory objects that reference other memory objects need to be updated with the new location information for those memory objects that will be moved. Relocation operation uses the new address information calculated by plan operation 114 to modify these memory objects, effectively updating all object reference information. Following relocate operation 122, all memory objects having references to other memory objects have updated information related to the new locations of the memory objects.

In the same ways that relocate operation 122 updates the information the memory objects for heap 54a, relocate operation 124 updates the memory reference information in the memory objects in heap 54b. Relocate operation 124, however, does not begin until rendezvous operation 120 indicates that all other plan operations are complete.

When a memory object in one heap, such as heap 54a, references an object in another heap, such as 54b, the object in heap 54a must be updated with information determined by the thread 104b, which operates on heap 54b. In order to do so, the garbage collection 104b maintains a directory, or other data structure indicating the previous address information and the new address information for the objects in heap 54b. In operation, relocate operation 122 analyzes the object in heap 54a and recognizes that the object references another object. Relocate operation 122 analyzes this information to determine which heap the referenced object is located, such as heap 54b. Once determined, relocate operation 122 analyzes the directory for that heap and using the old address value looks up the new address value. Using the new address value, the object reference is updated.

Since relocate operations 122 and 124 use information calculated by earlier plan operations 114 and 116 and since either relocate operations 122 and 124 could end up using information from other threads, neither relocate operation 122 or 124 starts before all other plan operations, such as plan operations 116 and 114 are completed.

5 Rendezvous points 118 and 120 ensure that other plan operations are complete before the relocate operations begin. In an embodiment, the relocate operations begin at approximately the same time. In another embodiment, relocate operations 122 and 124 may start at different times from each other, but not before all plan operations, such as plan operations 114 and 116 are complete.

10 Following the relocation operations 122 and 124, rendezvous points 126 and 128 temporarily pause threads 104a and 104b, respectively, until all other relocation phases are completed. Rendezvous points 126 and 128 are similar to points 110, 112, 118 and 120 in that rendezvous points 126 and 128 may deliver and receive information to and from the other rendezvous points, such as 128 and 126, respectively, to communicate
15 necessary information related to whether each thread has completed the preceding processes.

Once rendezvous operation 126 indicates that the relocation operation 122 is complete, compact operation 130 compacts the memory objects. Compact operation 130 physically moves information in the marked memory objects from one place to another,
20 compacting the memory objects so that no gaps exist between the memory objects. Such a sliding phase defragments the memory in the heap. The positioning of the objects is determined by the plan operation 114 and compact operation 130 carries out the movement to those final positions. Additionally, a memory pointer at the end of the

compacted memory objects can be used to indicate the physical location of the next free memory object for allocation. By moving all the live objects into a continuous set of memory address spaces, the remaining memory is deemed free and hence any garbage objects have been effectively collected.

5 A similar operation occurs in thread 104b. Following rendezvous operation 128, compact operation 132 compacts the live memory objects for heap 54b. Compact operation 132 is functionally similar to compact operation 130, since both move memory blocks according to compact the memory and fill any gaps between live memory objects. Compact operation 132 uses information calculated by plan operation 116 to move the
10 objects. Once the live objects have been compacted, a pointer at the end of the live objects provides the memory manager with the location of the free memory objects.

Following the compaction operations 130 and 132, rendezvous points 134 and 136 temporarily pause threads 104a and 104b, respectively, until all other compaction phases are completed. Since the memory is shared by all processing units, each thread
15 must wait for the others to complete before restarting any processes. Rendezvous points 134 and 136 are similar to points 110, 112, 118, 120, 126 and 128 discussed above in that rendezvous points 134 and 136 may deliver and receive information to and from the other rendezvous points, such as 136 and 134, respectively, to communicate necessary information related to whether each thread has completed the preceding processes.

20 In operation, each garbage collection phase for the different garbage collection threads may start at approximately the same time, following the completion of the previous phase by all the garbage collection threads. An exemplary timing diagram is shown in Fig. 5 and illustrates the relative timing different garbage collection threads,

such as 104a and 104b, of a two processing unit system, such as system 20 (Fig. 1). The example shown in Fig. 5 is intended as an example to illustrate start and stop times of different garbage collection phases and threads with respect to other garbage collection threads and no representation is made as to the accuracy of the scale of times for completing processes, phases or pauses.

In the timing example shown in Fig. 5, at time T_0 , application threads (1-N) are stopped and two garbage collection threads are started. At time T_1 , the second garbage collection thread completes the first phase of the garbage collection process, e.g., the marking phase, on its dedicated heap and any other cross-heap referenced memory objects. However, at T_1 , the first garbage collection thread has not completed the first phase. Therefore, the second garbage collection thread must wait until the first garbage collection thread completes the first phase before starting the second phase.

At time T_2 , the first garbage collection thread completes the first phase of the garbage collection process. Therefore, at time T_3 , both the first and second garbage collection threads may start the second phase. The time period between T_2 and T_3 represents the test operation 66 (Fig. 3) or the rendezvous point 110 and 112 (Fig. 4), wherein the two threads communicate in order to establish that the other threads have completed the preceding phase.

As shown in Fig. 5, at time T_3 , the second phase of the garbage collection process is started for both the first and second garbage collection threads. At T_4 , the first garbage collection thread completes the second phase of the garbage collection process, e.g., the planning phase, on its dedicated heap. However, at T_4 , the second garbage collection thread has not completed the second phase. Therefore, the first garbage collection thread

must wait until the second garbage collection thread completes the second phase before starting the third phase. At time T_5 , the second garbage collection thread completes the second phase of the garbage collection process. Therefore, at time T_6 , both the first and second garbage collection threads may start the third phase.

5 As before there is a small pause between the time when the last thread completes the present phase and when the next phase can begin, i.e., the time from T_5 and T_6 . Again, this time period represents the overhead in ensuring that all the threads have completed before starting the next phase.

10 Next, at time T_6 , the third phase of the garbage collection process is started for both the first and second garbage collection threads. At T_7 , the first garbage collection thread completes the third phase of the garbage collection process, e.g., the relocation phase, on its dedicated heap. However, at T_7 , the second garbage collection thread has not completed the third phase. Therefore, the first garbage collection thread must wait until the second garbage collection thread completes the third phase before starting the
15 final phase. At time T_8 , the second garbage collection thread completes the third phase of the garbage collection process. Therefore, at time T_9 , both the first and second garbage collection threads may start the final phase.

20 As before, there is a small pause between the time when the last thread completes the present phase and when the next phase can begin, i.e., the time from T_8 and T_9 . Again, this time period represents the overhead in ensuring that all the threads have completed before starting the next phase.

 Last, at time T_9 , the final phase of the garbage collection process is started for both the first and second garbage collection threads. At T_{10} , the second garbage collection

thread completes the final phase of the garbage collection process, e.g., the compaction phase, on its dedicated heap. However, at T_{10} , the first garbage collection thread has not completed the final phase. Therefore, the second garbage collection thread must wait until the first garbage collection thread completes the final phase before ending the process. At time T_{11} , the first garbage collection thread completes the final phase of the garbage collection process. Therefore, at time T_{12} , both the first and second garbage collection threads are complete and the application threads 1-N may be restarted.

A small pause exists between the completion time of the last thread of the present phase T_{11} and when the next application thread can be restarted at time T_{12} . Again, this time period represents the overhead in ensuring that all the threads have completed before restarting the application thread.

In order to reduce the relative wait times (e.g., the time T_1 to T_2 during the marking phase shown in Fig. 5) for the processing units, the memory managers attempt to balance the heaps. Balancing the heaps generally relates to allocating relatively even amounts of memory objects to the different heaps. One method of balancing heaps involves allocating new threads to the processing unit maintaining the heap having the smallest amount of allocated memory space. This process may work especially well in a server system designed to handle large numbers of requests, wherein each new request is a new thread and wherein all threads have similar memory requirements. Many other balancing algorithms may be employed in other embodiments.

The above described system and method provides the ability to use all the processors in a multiprocessor system to perform garbage collection which may significantly reduce the garbage collection process time. Using all the processors may

require that each processor perform a few extra instructions to maintain a relatively synchronized garbage collection process but the added instructions are relatively minor compared to the overall increase in speed by having all processors operating during this time. Additionally, the above system is highly scalable since more processing units may
5 be added without significantly changing the garbage collection process. That is, the number of processing units in the system does not limit the process outlined above.

Although the invention has been described in language specific to structural features, methodological acts, and computer readable media containing such acts, it is to be understood that the invention defined in the appended claims is not necessarily limited
10 to the specific structure, acts or media described. As an example, other garbage collection techniques that use marking can benefit from the principles of the present invention. Therefore, the specific structure, acts or media are disclosed as preferred forms of implementing the claimed invention.

Claims

What is claimed is:

1. A method of collecting garbage in a computer system having a memory and a plurality of multiprocessors that share the memory, the method comprising:

logically dividing the memory into a plurality of heaps, each heap dedicated to one processor for garbage collection;

5 performing a plurality of garbage collection phases, wherein each processor having a dedicated heap, each processor performs each of the phases on the heap dedicated to the processor using a garbage collection thread executing on the processor;

and

synchronizing the processors so that all processors have completed the preceding
10 phase prior to each processor beginning the next phase.
2. A method as defined in claim 1 wherein the synchronizing act comprises:

for each processor performing a phase of the garbage collection process, upon completion of the phase of the garbage collection process waiting for the other processors to complete the phase of the garbage collection process; and

5 once the other processors have completed the phase of the garbage collection process, beginning the next phase of the garbage collection process.
3. A method as defined in claim 2 wherein the garbage collection phases further comprise:

a marking phase that marks all reachable objects in memory;

a planning phase that plans the relocation of the objects;

5 a relocation phase that updates the object references based on information
calculated by the planning phase; and

 a compaction phase that compacts the reachable objects in memory.

4. A method as defined in claim 3 wherein the planning phase maintains a directory
of object references and wherein the relocation phase further comprises:

 analyzing each memory object to retrieve references to other memory objects;

 if a reference to another memory object is present, analyzing the reference

5 information to determine which heap the referenced object is associated;

 analyzing the directory of the heap for the referenced object to determine a new
address location of the referenced object; and

 updating the reference information in the memory object.

5. A method of performing garbage collection in a computer system having a shared
memory and a plurality of processing units, wherein the memory is divided into heaps
and each heap is associated with a single processing unit, said method comprising:

 stopping executing process threads;

5 initiating parallel marking threads in each processing unit associated with a heap,
wherein one thread executes within each processing unit and wherein the marking threads
mark the reachable objects in the shared memory;

 upon completion of all marking threads, initiating parallel planning threads in
each processing unit associated with a heap, wherein one thread executes within each
10 processing unit and wherein each planning thread plans the new locations for objects
within the associated heap;

upon completion of all the planning threads, initiating parallel relocating threads in each processing unit associated with a heap, wherein one thread executes within each processing unit and wherein each relocating thread updates internal object references
15 based on the new locations determined by the planning threads, the relocation threads updating information for objects within the associated heap; and

upon completion of all the relocating threads, initiating parallel compacting threads in each processing unit associated with a heap, wherein one thread executes within each processing unit and wherein each compacting thread updates moves objects
20 within the associated heap to the new locations determined by the planning threads.

6. A method as defined in claim 5 wherein the planning phase maintains a directory of object references and wherein the relocation phase further comprises:

analyzing each memory object to retrieve references to other memory objects;
if a reference to another memory object is present, analyzing the reference
5 information to determine which heap the referenced object is associated;
analyzing the directory of the heap for the referenced object to determine a new address location of the referenced object; and
updating the reference information in the memory object.

7. A method as defined in claim 5 wherein the marking threads mark objects independently of the heap boundaries.

8. A method as defined in claim 5 wherein all the processing units associated with the computer system are associated with a heap.

9. A method as defined in claim 5 wherein the heaps comprise a contiguous set of memory objects within the shared memory.

10. A system for performing garbage collection in a shared memory environment, the shared memory being accessed by a plurality of processing units, the shared memory divided into heaps and each heap is associated with one processing unit, the system comprising:

5 for each processing unit associated with a heap:

a marking module executing a marking phase that marks reachable objects within the shared memory;

a planning module for executing a planning phase that plans the relocation the memory objects within the associated heap following the marking of all reachable
10 objects;

a relocating module for executing a relocating phase that updates the object references within objects of the associated heap following the planning of the relocation;

a compacting module for executing a compacting phase that moves the
15 memory objects of the associated heap following the updating of the object references;
and

a rendezvous module for determining whether all processing units in the system have completed each preceding phase before starting the next phase.

11. A computer program product readable by a computer and encoding instruction for executing a computer process for collecting garbage in a computer system having a memory and a plurality of multiprocessors that share the memory, the process comprising:

5 logically dividing the memory into a plurality of heaps, each heap dedicated to one processor for garbage collection;

 performing a plurality of garbage collection phases, wherein each processor having a dedicated heap performs each of the phases using a garbage collection thread executing on the processor; and

10 synchronizing the processors so that each processor has completed the preceding phase prior to beginning the next phase.

12. A computer program product as defined in claim 11 wherein the synchronizing act comprises:

 for each processor performing a phase of the garbage collection process, upon completion of the phase of the garbage collection process waiting for the other processors
5 to complete the phase of the garbage collection process; and

 once the other processors have completed the phase of the garbage collection process, beginning the next phase of the garbage collection process.

13. A computer program product as defined in claim 12 wherein the garbage collection phases further comprise:

 a marking phase that marks all reachable objects in memory;

 a planning phase that plans the relocation of the objects;

5 a relocation phase that updates the object references based on information calculated by the planning phase; and

 a compaction phase that compacts the reachable objects in memory.

14. A computer program product as defined in claim 13 wherein the planning phase maintains a directory of object references and wherein the relocation phase further comprises:

analyzing each memory object to retrieve references to other memory objects;

5 if a reference to another memory object is present, analyzing the reference information to determine which heap the referenced object is associated;

analyzing the directory of the heap for the referenced object to determine a new address location of the referenced object; and

updating the reference information in the memory object.

15. A computer program product readable by a computer and encoding instruction for executing a computer process for performing garbage collection in a computer system having a shared memory and a plurality of processing units, wherein the memory is divided into heaps and each heap is associated with a single processing unit, said process
5 comprising:

stopping executing process threads;

initiating parallel marking threads in each processing unit associated with a heap, wherein one thread executes within each processing unit and wherein the marking threads mark the reachable objects in the shared memory;

10 upon completion of all marking threads, initiating parallel planning threads in each processing unit associated with a heap, wherein one thread executes within each processing unit and wherein each planning thread plans the new locations for objects within the associated heap;

19. A computer program product as defined in claim 15 wherein the heaps comprise a contiguous set of memory objects within the shared memory.

20. A runtime environment for a multiprocessor system, the multiprocessor system having a plurality of processing units and a shared memory, the shared memory divided into a plurality of heaps wherein each heap is dedicated to one processing unit; the runtime environment comprising:

5 a plurality of garbage collection modules for reclaiming unused memory objects located within the shared memory, each garbage collection module associated with a processing unit, each garbage collection module operates on a dedicated heap of memory; and

10 a synchronizing module for synchronizing the activities performed by the garbage collection modules.

METHOD AND SYSTEM FOR MULTIPROCESSOR GARBAGE COLLECTION

Abstract of the Invention

A garbage collection system and method in a multiprocessor environment having a shared memory wherein two or more processing units participate in the reclamation of garbage memory objects. The shared memory is divided into regions or heaps and all heaps are dedicated to one of the participating processing units. The processing units generally perform garbage collection operations, i.e., a thread on the heap or heaps that are dedicated to that the processing unit. However, the processing units are also allowed to access and modify other memory objects, in other heaps when those objects are referenced by and therefore may be traced back to memory objects within the processing units dedicated heap. The processors are synchronized at rendezvous points to prevent reclamation of used memory objects.




Fig. 1

+




Fig. 3

+




Fig. 4

+




Fig. 5

+

MERCHANT & GOULD P.C.

United States Patent Application

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor I hereby declare that my residence, post office address and citizenship are as stated below next to my name; that

I verily believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled METHOD AND SYSTEM FOR MULTIPROCESSOR GARBAGE COLLECTION, the specification of which I have reviewed and for which I solicit a United States patent is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56 (attached hereto).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on the basis of which priority is claimed:

- a. ☒ no such applications have been filed.
b. ☐ such applications have been filed as follows:

FOREIGN APPLICATION(S), IF ANY, CLAIMING PRIORITY UNDER 35 USC § 119			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)
ALL FOREIGN APPLICATION(S), IF ANY, FILED BEFORE THE PRIORITY APPLICATION(S)			
COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)

I hereby claim the benefit under Title 35, United States Code, § 120/365 of any United States and PCT international application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. APPLICATION NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below:

U.S. PROVISIONAL APPLICATION NUMBER	DATE OF FILING (Day, Month, Year)

I hereby appoint the following attorney(s) and/or patent agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith:

Albrecht, John W.	Reg. No. 40,481	Lacy, Paul E.	Reg. No. 38,946
Ali, Jeffer M.	Reg. No. 46,359	Larson, James A.	Reg. No. 40,443
Anderson, Gregg I.	Reg. No. 28,828	Liepa, Mara E.	Reg. No. 40,066
Batzli, Brian H.	Reg. No. 32,960	Lindquist, Timothy A.	Reg. No. 40,701
Beard, John L.	Reg. No. 27,612	Lycke, Lawrence E.	Reg. No. 38,540
Berns, John M.	Reg. No. 43,496	McAuley, Steven A.	Reg. No. P-46,084
Black, Bruce E.	Reg. No. 41,622	McDonald, Daniel W.	Reg. No. 32,044
Branch, John W.	Reg. No. 41,633	McIntyre, Jr., William F.	Reg. No. P-44,921
Bremer, Dennis C.	Reg. No. 40,528	Mueller, Douglas P.	Reg. No. 30,300
Bruess, Steven C.	Reg. No. 34,130	Pauly, Daniel M.	Reg. No. 40,123
Byrne, Linda M.	Reg. No. 32,404	Phillips, Bryan K.	Reg. No. P46,990
Carlson, Alan G.	Reg. No. 25,959	Phillips, John B.	Reg. No. 37,206
Caspers, Philip P.	Reg. No. 33,227	Plunkett, Theodore	Reg. No. 37,209
Chiapetta, James R.	Reg. No. 39,634	Prendergast, Paul J.	Reg. No. 46,068
Clifford, John A.	Reg. No. 30,247	Pytel, Melissa J.	Reg. No. 41,512
Daignault, Ronald A.	Reg. No. 25,968	Qualey, Terry	Reg. No. 25,148
Daley, Dennis R.	Reg. No. 34,994	Reich, John C.	Reg. No. 37,703
Dalglish, Leslie E.	Reg. No. 40,579	Reiland, Earl D.	Reg. No. 25,767
Daulton, Julie R.	Reg. No. 36,414	Schmaltz, David G.	Reg. No. 39,828
Devries Smith, Katherine M.	Reg. No. 42,157	Schuman, Mark D.	Reg. No. 31,197
DiPietro, Mark J.	Reg. No. 28,707	Schumann, Michael D.	Reg. No. 30,422
Edell, Robert T.	Reg. No. 20,187	Scull, Timothy B.	Reg. No. 42,137
Epp Ryan, Sandra	Reg. No. 39,667	Sebald, Gregory A.	Reg. No. 33,280
Glance, Robert J.	Reg. No. 40,620	Skoog, Mark T.	Reg. No. 40,178
Goggin, Matthew J.	Reg. No. 44,125	Spellman, Steven J.	Reg. No. 45,124
Goffa, Charles E.	Reg. No. 26,896	Stoll-DeBell, Kirstin L.	Reg. No. 43,164
Gorman, Alan G.	Reg. No. 38,472	Sumner, John P.	Reg. No. 29,114
Gould, John D.	Reg. No. 18,223	Swenson, Erik G.	Reg. No. 45,147
Gregson, Richard	Reg. No. 41,804	Tellekson, David K.	Reg. No. 32,314
Gresens, John J.	Reg. No. 33,112	Trembath, Jon R.	Reg. No. 38,344
Hammer, Samuel A.	Reg. No. P46,754	Tuchman, Ido	Reg. No. 45,924
Hamre, Curtis B.	Reg. No. 29,165	Underhill, Albert L.	Reg. No. 27,403
Hertzberg, Brett A.	Reg. No. 42,660	Vandenburgh, J. Derek	Reg. No. 32,179
Hillson, Randall A.	Reg. No. 31,838	Wahl, John R.	Reg. No. 33,044
Holzer, Jr., Richard J.	Reg. No. 42,668	Weaver, Karrie G.	Reg. No. 43,245
Johnston, Scott W.	Reg. No. 39,721	Welter, Paul A.	Reg. No. 20,890
Kadievitch, Natalie D.	Reg. No. 34,196	Whipps, Brian	Reg. No. 43,261
Karreker, Shaukat	Reg. No. 34,049	Wickhem, J. Scot	Reg. No. 41,376
Kastelic, Joseph M.	Reg. No. 37,160	Williams, Douglas J.	Reg. No. 27,054
Kettelberger, Denise	Reg. No. 33,924	Witt, Jonelle	Reg. No. 41,980
Keys, Jeramie J.	Reg. No. 42,724	Wu, Tong	Reg. No. 43,361
Knearl, Homer L.	Reg. No. 21,197	Xu, Min S.	Reg. No. 39,536
Kowalchyk, Alan W.	Reg. No. 31,535	Zeuli, Anthony R.	Reg. No. P45,255
Kowalchyk, Katherine M.	Reg. No. 36,848		

In addition, I also hereby appoint the following attorneys to prosecute this application and to transact all business in the U.S. Patent and Trademark Office in connection therewith:

Kate E. Sako, Reg. No. 32,628
Daniel D. Crouse, Reg. No. 32,022

I hereby authorize them to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/ organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct Merchant & Gould P.C. to the contrary.

Please direct all correspondence in this case to Merchant & Gould P.C. at the address indicated below:

Homer L. Knearl
Merchant & Gould P.C.
P.O. Box 2903
Minneapolis, MN 55402-0903
303.357.1633

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

2	Full Name Of Inventor	Family Name Dussud	First Given Name Patrick	Second Given Name H.
0	Residence & Citizenship	City Bellevue	State or Foreign Country Washington	Country of Citizenship United States of America
1	Post Office Address	Post Office Address 6008 142nd Ct SE	City Bellevue	State & Zip Code/Country Washington 98006/USA
Signature of Inventor 201: <i>Patrick Henry Dussud</i>			Date: <i>7/27/00</i>	

§ 1.36 Duty to disclose information material to patentability.

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith in dealing with the Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned. Information material to the patentability of a claim that is canceled or withdrawn from consideration need not be submitted if the information is not material to the patentability of any claim remaining under consideration in the application. There is no duty to submit information which is not material to the patentability of any existing claim. The duty to disclose all information known to be material to patentability is deemed to be satisfied if all information known to be material to patentability of any claim issued in a patent was cited by the Office or submitted to the Office in the manner prescribed by §§ 1.97(b)-(d) and 1.98. However, no patent will be granted on an application in connection with which fraud on the Office was practiced or attempted or the duty of disclosure was violated through bad faith or intentional misconduct. The Office encourages applicants to carefully examine:

- (1) prior art cited in search reports of a foreign patent office in a counterpart application, and
 - (2) the closest information over which individuals associated with the filing or prosecution of a patent application believe any pending claim patentably defines, to make sure that any material information contained therein is disclosed to the Office.
- (b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and
- (1) It establishes, by itself or in combination with other information, a prima facie case of unpatentability of a claim;
- or
- (2) It refutes, or is inconsistent with, a position the applicant takes in:
 - (i) Opposing an argument of unpatentability relied on by the Office, or
 - (ii) Asserting an argument of patentability.

A prima facie case of unpatentability is established when the information compels a conclusion that a claim is unpatentable under the preponderance of evidence, burden-of-proof standard, giving each term in the claim its broadest reasonable construction consistent with the

specification, and before any consideration is given to evidence which may be submitted in an attempt to establish a contrary conclusion of patentability.

(c) Individuals associated with the filing or prosecution of a patent application within the meaning of this section are:

(1) Each inventor named in the application:

(2) Each attorney or agent who prepares or prosecutes the application; and

(3) Every other person who is substantively involved in the preparation or prosecution of the application and who is associated with the inventor, with the assignee or with anyone to whom there is an obligation to assign the application.

(d) Individuals other than the attorney, agent or inventor may comply with this section by disclosing information to the attorney, agent, or inventor.